



# MAX 600°C

用於金屬件退火,回火熱處理, 循環運風式, 溫度分布均勻, 選用雙層式隔熱材料, 爐膛採用不銹鋼製造, 可控硅整流調溫, 快速升溫,

Air circulation type furnaces built with double-layer insulating material, stainless steel chamber with PID control. Well-distributed temperature and rapid heat up, suitable for tempering and annealing of metal.

SCS - 600 恒溫櫃式焗爐  
SCS - 600 Chamber Furnaces

型號 Model	爐內呎吋 (cm) Inside Dimension H: W: D:	爐外呎吋 (cm) Outside Dimension H: W: D:	最高溫度 Maximum Temperature	發熱功率 Power (for heater)	總電流 Current	輸入電 壓 Input Voltage	層架托位 Shelf Support	概略重量 About Weight
SCS-1	60*60*45	160*110*90	600°C	12KW	20A	380V 3Ø	4	430KG
SCS-2	75*75*50	175*125*90	600°C	15KW	25A	380V 3Ø	5	480KG
SCS-3	90*100*75	190*150*115	600°C	18KW	30A	380V 3Ø	6	550KG
SCS-4	100*120*75	200*170*115	600°C	24KW	40A	380V 3Ø	6	680KG

- ▲ 如有資料變更,恕不另行通知
- ▲ Information to change without prier notice